



# ACCESS

UNSCRAMBLERS WITH ACCESSIBLE ENCLOSURE



The ACCESS system has an **enclosure** which enables **full access to the interior** of the unit, for **ease of inspection, maintenance and cleaning tasks**.

When in operation, its multiple windows allow you to see from the outside what is happening at any time, and to **inspect** the unit **without having to stop production**.

ACCESS ensures full visibility with «zero» access to moving parts. Its safety system prevents the opening of doors, windows and access panels while the machine is running.



UNSCRAMBLERS WITH ACCESSIBLE ENCLOSURE

## Description of the enclosure

Enclosure is completely closed: «zero» access

Two types of sound insulation: 80 dB(A) or 75 dB(A)

Panels that **only open when the machine is not running**: **maximum safety**

Two types of enclosure panel finish: **plastic coated steel** or **AISI 304 stainless steel**

Multiple windows: **enable constant control of the unit interior without stopping the line**



Stainless steel enclosure for unscrambler Model N-35 with integrated feed silo



Stainless steel enclosure for unscrambler Model POSIPUCKS-15



Stainless steel enclosure for unscrambler Model N-12



Plastic coated steel enclosure for unscrambler Model MONOCHUTE-45 with integrated rotary orientor

## Advantages of POSIMAT

The ACCESS enclosure can be installed with manual changeover units «N», adjustable units, such as POSIFLEX-A (automatic adjustment) or POSIFLEX-M (manual adjustment), and Monochute and Multichute units. For more information on these changeover and unscrambling systems, see the corresponding catalogues or contact us.